



Technology Solutions

TEK-BAR 3110A

Explosion-Proof Differential Pressure Transmitter



PRESSURE



Introduction

The Tek-Bar 3110A Explosion-Proof Differential Pressure Transmitter have excellent stability, high accuracy, and include features that facilitate easy installation, start up, and minimum maintenance thereby lowering process downtime and overall cost of ownership in the long run. These transmitters are equipped with an automatic temperature compensation function integrated into its advanced signal processing circuitry to ensure high reliability and performance corresponding to change of ambient temperature.

Measuring Principle

The Tek-Bar 3110A Explosion-Proof Differential Pressure Transmitter uses Capacitance pressure sensors. It consists of two metal plates that are separated by sensing diaphragm. An electrically insulating fill fluid (silicon oil), transfers the movement from isolating diaphragm to the sensing diaphragm. The capacitance characteristics of the sensing element changes. These signal transfer to the electronic circuitry of transmitter that converts the change in capacitance to the output signal. Capacitance transmitters are configured for differential pressure measurement. Usual outputs are voltage or current.

Capacitance can be calculated using the formula:

$$C = \frac{\epsilon(A)}{d}$$


Where,

C- Capacitance,

ϵ -Dielectric Constant

A-Area of plate


d-Distance between capacitor plates



Operation

Electronic Module:

The Electronics module consists of a circuit board sealed in an enclosure. It consists of a MCU module, a power module, an analog module, a LCD module and a terminal module. The MCU module acquires the digital value from the analog module and applies correction coefficients selected from EEPROM. The output section of the power module converts the digital signal to a 4 to 20 mA output. The MCU module communicates with the HART based Configurator. The Power module have a DC-to-DC power conversion circuit and an Input/output isolation circuit. An optional LCD module plugs into the MCU module and displays the digital output in the user-configured unit.



Sensor Input:

The model Tek-Bar 3110A Explosion-Proof Differential Pressure Transmitter uses capacitance type pressure sensor. The transmitter is used in level and flow applications.

The sensor module converts the capacitance or the resistance to the digital value. The MCU module calculates the process pressure based on the digital value.

The sensor modules include the following features

- The software of the transmitter compensates for the thermal effects, improving performance.
- Precise Input Compensation during operation is achieved with temperature and pressure correction coefficients that are characterized over the range the transmitter and stored in the sensor module EEPROM memory
- EEPROM stores sensor information and correction coefficients separately from MCU module, allowing for easy repair, reconfiguration and replacement

Features/Benefits


- Operator can calibrate device using zero/span button, no handheld calibrator required. Optionally handheld device communicator can be used to calibrate devices.
- Digital communication HART protocol, latest version
- Fail-safe mode process function for detecting any abnormal condition occurring
- Standard accuracy $\pm 0.075\%$, High enhanced Accuracy $\pm 0.04\%$ available.
- Automatic ambient temperature compensation improve performance of device
- It can be used as flow meter and should be installed vertically without using additional flanges
- Various Output: 4-20 mA, digital signals
- The mounting bracket can be rotated up to 360° and LCD display up to 270°

Applications

- It can be used as a flowmeter; it can check flow rate and total flow
- Level monitoring
- Used to measure liquid, gas, and steam flow

Dimensional Drawing

Standard Model



Specifications

Technical Specification

Parameter	Description
Accuracy	0.075% of Span standard, High enhanced accuracy $\pm 0.04\%$ of span available in conformance to ± 3 Sigma
Turndown	100:1
Stability	5 years standard, Optional 3 year $\pm 0.10\%$ of URL available
Maximum Working Pressure	2000 psi std, High Pressure 4500 psig available
Hydrostatic Test Pressure	1.5 times MWP
Burst Pressure	10000 psig (68.9MPa)
Process Temperature Limits	-40 °F to +248 °F
Ambient Temperature Effect	$\pm [0.019\% \text{URL} + 0.125\% \text{Span}] / 82.4 \text{ °F}$
Ambient Temperature	-40 °F to +185 °F
Humidity Limits	5% to 100% RH
Power Supply Effects	$\pm 0.005\%$ of Span per Volt
Mounting Position Effects	Zero Shift up to 350Pa No Span Effect
Display (Optional)	5 digit LCD display
Failure Mode	Fail High: Current $\geq 21.1 \text{ mA}$
	Fail Low: Current $\leq 3.78 \text{ mA}$
Damping Time	0.25 to 60 sec
Volumetric Displacement	$< 0.005 \text{ cu in}$
Vibration Effect	$\pm 0.1\%$ of URL per IEC60770-1 site conditions
EMC Immunity	EN50081-2, EN50082-2, IEC801-3

Electrical Specification

Parameter	Description
Power Supply	12 to 45 VDC
HART loop resistance	250 to 550 ohm
Output Signal	4 mA to 20 mA or HART®
Isolation	500 Vrms (707 VDC)

Physical Specifications

Parameter	Description
Isolating Diaphragm	316LSST
Drain and Vent Valve	316SST
Flange and Adapter	316SST
O-ring	Viton, PTFE
Fill Fluid	Silicone oil or Inert fill
Paint	Epoxy-Polyester or Polyuret
Mounting Bracket	304SST with U-bolt (304SST) for 2-inch pipe
Nameplate	304SST
Electronic Housing	Aluminum (Option:316LSST)
Bolts and Bolting Flange	304SST
Process Connection Size	¼" NPT Female
Electrical Connections	½" NPT Female
Weight (excluding Option Items)	8.589 lb (Standard)
	11.882 lb (SST Housing)
2" Pipe Stanchion Type bracket	Angle or Flat type
Approvals	FM (Class I Div I)


Measuring Range Limit For Tek-Bar 3110A

Range Code	Calibrated Span (Min. to Max.)		Lower Range Limit		Upper Range Limit	
3	0.6 to 30 in w.c	0.15 to 7.5 kPa	-30 in w.c.	-7.5 kPa	30 in w.c.	7.5 kPa
4	1.5 to 150 in w.c	0.373 to 37.3 kPa	-150 in w.c.	-37.3 kPa	150 in w.c.	37.3 kPa
5	7.5 to 750 in w.c	1.865 to 186.5 kPa	-750 in w.c.	-186.5 kPa	750 in w.c.	186.5 kPa
6	1 to 100 psi	6.9 to 690 kPa	-100 psi	-690 kPa	100 psi	690 kPa
7	3 to 300 psi	20.68 to 2068 kPa	-300 psi	-2068 kPa	300 psi	2068 kPa

Installation


Liquid Flow Measurement

- Place taps to the side of the line to prevent sediment deposits on the transmitters process isolators
- Mount the transmitter beside or below the taps so gases can vent into the process line
- Mount drain/vent valve upward to allow gases to vent




Gas Flow Measurement

- Place taps in the top or side of the line
- Mount the transmitter beside or above the taps so liquid will drain into the process line



Steam Flow Measurement

- Place taps to the side of the line.
- Mount the transmitter below the taps to ensure that the impulse piping will stay filled with condensate.
- In steam service above 250 °F (121 °C), fill impulse lines with water to prevent the steam from contacting the transmitter directly and to ensure accurate measurement at start-up.



Note: For steam or other elevated temperature services, it is important that temperatures at the process connection do not exceed the transmitters process temperature limits.

Model Chart

Example	Tek-Bar 3110A	D	3	FM	1	SS	1	LCD	Tek-Bar 3110A-D-3-FM-1-SS-1-LCD
Series	Tek-Bar 3110A								Explosion-Proof Differential Pressure Transmitter
Sensor Type		D A G							Differential Pressure Absolute Pressure Gauge Pressure
Range Options			3 4 5 6 7						0-30" w.c. 0-150" w.c. 0-750" w.c. 0-100psid 0-300psid
Approval Rating				FM ATEX					FM Approval (Class I Div I) ATEX Flameproof or ATEX Intrinsic Safe Approval
Process Connection					1 x				¼" NPT Female Diaphragm Seal
Diaphragm Material						SS			316 Stainless Steel
Electrical Connection							1		½" NPT Female
Options									LCD 5 Digit LCD (Local Indication Only) B Blind Unit SSH 316 Stainless Steel Housing CC Custom Calibration with 5 point Calibration Certificate FC Factory Configuration, No Certificate (Need customer range) BA Stainless Steel Bracket (Angle type) with SST Bolts BF Stainless Steel Bracket (Flat type) with SST Bolts TAG Custom etching of the name plate (Must specify on P.O.) LP Lighting Protection LV 12VDC, Low Volt, 4-wire, 1-5 VDC output, No HART (Must include option MFI) O ½"-14 NPTF, Oval Flange Process Connection Adapter (Includes 2 O-Rings, an adapter, and 2 bolts) EA ±0.04% enhanced accuracy with 3 year stability H High Static Pressure 4500psig

Popular Models

Model Number	Description
3110A-D-3-FM-1-1-LCD	Explosion-proof DP Pressure Transmitter, 0-30" w.c., LCD
3110A-D-4-FM-1-1-LCD	Explosion-proof DP Pressure Transmitter, 0-150" w.c., LCD
3110A-D-5-FM-1-1-LCD	Explosion-proof DP Pressure Transmitter, 0-750" w.c., LCD
3110A-D-6-FM-1-1-LCD	Explosion-proof DP Pressure Transmitter, 0-100 psid, LCD
3110A-D-7-FM-1-1-LCD	Explosion-proof DP Pressure Transmitter, 0-300 psid, LCD

Customer Service & Support




TEK-TROL LLC reserves the right to change the designs and/or materials of its products without notice. The contents of this publication are the property of TEK-TROL LLC and cannot be reproduced by any other party without written permission. All rights reserved. Copyright © 2021 TEK-TROL LLC
TEK-TROL LLC
DOC # TEK/TIPS/CAT/240606/3110A/004




www.tek-trol.com

Tek-Trol LLC

796 Tek Drive Crystal Lake,
IL 60014, USA

 +1 847-857-6076

 tektrol@tek-trol.com

 www.tek-trol.com

Tek-Trol is a fully owned subsidiary of TEKMATIION LLC. We offer our customers a comprehensive range of products and solutions for process, power and oil & gas industries. Tek-Trol provides process measurement and control products for Flow, Level, Temperature & Pressure measurement, Control valves & Analyzer systems. We are present in 15 locations globally and are known for our knowledge, innovative solutions, reliable products and global presence.